



- very rugged
- two simultaneous channels
- reliable
- operating temperature up to +140°C
- inductive power supply
- high accuracy
- simple installation




2-CHANNEL-TELEMETRY SYSTEM

for strain gauge measurement on rotating parts

AXON Systems Ltd. - Wildmoos 5 - 82266 Inning a. Ammersee - Germany
www.axon-systems.com - info@axon-systems.com
 Tel.: +49 (0) 8143- 24 198- 0 - Fax: +49 (0) 8143 24 198- 90

Telemetry System AXON J2D



The telemetry system AXON J2D transmits the signals of two independent strain gauges. The amplified signals are made available on the Control Unit for further recording. The quality of the received digital data stream is constantly monitored, regulated and displayed via RSSI output. Thus, the telemetry system offers the possibility to simultaneously measure two strain gauge signals in the smallest space and transmit them contactless.



Rotor Unit:

Supplies the sensor with high-precision voltage, captures and processes the data from the strain gauge and transmits the fully digitised data stream contactless between the rotating shaft and the Stator Unit.



Control Unit:

The central control unit and data output of the telemetry system. Generates the inductive supply voltage for the rotor unit and reproduces the data measured on the shaft as a voltage signal. Inductive supply and RF data reception are monitored and always controlled during operation to ensure the best possible data transmission.




Stator Unit:

Produces the dynamic inductive field which supplies power to the Rotor Unit on the rotating shaft. Simultaneously it receives the digital data stream from the shaft. Distances up to 70mm between rotor and stator antenna can be realized. Axial and radial relative movements between stator and rotor are covered in an range of several centimeters⁽¹⁾.

(1) Depending on application

Telemetry System AXON J2D



The ideal system for strain gauge based 2-channel measurements

The J2D telemetry system is the perfect basis for highly professional combined strain gage measurements (such as torque and force) that deliver stable and highly accurate measurement data, even under the toughest conditions. Whether in vehicle testing or on the test bench- AXON telemetry systems deliver reliable measurement results under a wide variety of applications.

The highly effective inductive power supply of the rotating components allows an uninterrupted use even under harsh conditions.

Even in oil, a stable power- and data transmission is ensured.

The distance between the stator and rotor antenna can easily vary between 1 and 70mm⁽¹⁾.

The intelligent inductive power transmission IPT continuously optimizes the rotor supply voltage during operation.

In addition, the RSSI output⁽²⁾ of the Control Unit provides information about the quality of the received data stream.

1) Depending on application

2) Receive Signal Strength Indicator

Strain gauge based measurements on:




- Drive shafts
- Prop shafts
- Torque Flanges
- Rotating gearbox parts
- and many more



Telemetry System AXON J2D

Rotor Units



Type	J2D-RD13	J2D-RD13T	J2D-RD13H
Signal conditioning channel 1	Strain gauge full bridge		
Signal conditioning channel 2	Strain gauge full bridge		
Power supply	inductive or battery		
Modulation	PCM (digital)		
Resolution	12 bit (pure data stream)		
Sampling	5,2kSa/s per channel		
Housing	Aluminium		
Connections	Solder Pads		
Dimensions	65 x 19 x 7 mm		
Operating temperature	-40°C +105°C	-40°C +125°C	-40°C +140°C
Carrier frequency (standard)	13,6 MHz		
Carrier frequencies (optional)	12,6 MHz, 14,6 MHz, 15,6 MHz		
Weight	14 grams		
Measurement range	0,1 - 500 mV/V adjustable		
Degree of protection	IP67 with protectional covering of solder pads		
Conformity	CE		



Accessories

J2D-RX-ADA

Adapter board for rotor unit J2D / J2DT with miniature screw terminals; flexible in the longitudinal direction; Dimensions: 71 x 20 x 61mm




Telemetry System AXON J2D

Stator Units

Standard-ringstator

Type	JXD-SR70	JXD-SR70T
Type of transmission	inductively with conductor loop (transmission coil)	
Transmission coil	copper free shapeable Ø 40 1000mm	
Transmission distance	0 70 mm ⁽¹⁾	
RF-Reception	wideband (10 MHz 30 MHz)	
Housing	Aluminium	
Connections	Fischer 4-pole, IP68	
Dimensions (incl. connections)	63 x 50 x 34,5 mm	
Operating temperature	-40°C +105°C	-40°C +125°C
Cable length Stator - Control Unit	5m; optional 7m, 8m, 10m, 30m, 50m any cable length up to 200m on request	
Weight	187 grams	
Degree of protection	IP68	
Conformity	CE	



Ringstator for high EMC loaded environments

Type	JXD-SR70E	JXD-SR70TE
Type of transmission	inductively with conductor loop (transmission coil), additional EMC-terminal for signal analysis and suppression of disturbance fields	
Transmission coil	EMC-stator coil JX-ECE02 Ø 40 1000mm	
Transmission distance	0 70 mm ⁽¹⁾	
RF-Reception	wideband (10 MHz 30 MHz)	
Housing	Aluminium	
Connections	Fischer 4-pole, IP68	
Dimensions (incl. connections)	63 x 50 x 34,5 mm	
Operating temperature	-40°C +105°C	-40°C +125°C
Cable length Stator - Control Unit	5m; optional 7m, 8m, 10m, 30m, 50m any cable length up to 200m on request	
Weight	189 grams	
Degree of protection	IP68	
Conformity	CE	

(1) Depending on application






Especially for use in vehicles
with electric drive and high
EMC load

recommended accessory

JX-ECE02

Free shapeable transmission coil for stator units JX(D)-SR70(T)E with additional EMC-terminal.
Length 1m, shortenable





Telemetry System AXON J2D

Stator Units

Inductive-Stator without transmission coil

Typ	JXD-SE60	JXD-SE60T
Type of transmission	inductive as Pick-Up	
RF-Reception	wideband (10 MHz 30 MHz)	
Housing	Plastic	
Transmission distance	0 60 mm ⁽¹⁾	
Dimensions (without cable)	63 x 50 x 34,5mm	
Operating temperature	-40°C +105°C	-40°C +125°C
Cable length Stator - Control Unit	5m; optional 7m, 8m, 10m, 30m, 50m any cable length up to 200m on request	
Weight	220 grams	
Degree of protection	IP68	
Conformity	CE	

(1) Depending on application







Telemetry System AXON J2D

Control Unit

Type	J2D-CE13
Dimensions	205 x 105 x 35mm (incl. connectors)
Supply voltage	9 - 36 VDC
Signal bandwidth	1000 Hz (-3dB)
Signal output strain gauge	2 x BNC; analog Voltage $\pm 10V$
Carrier frequency (standard)	13,6 MHz
Carrier frequency (optional)	12,6 MHz, 14,6 MHz, 15,6 MHz
Offset correction	$\pm 0,5V$, by Poti
Signal propagation delay	450 μs
Wireless shunt cal	Shunt Cal push button on Control Unit
Degree of protection	IP40
Weight	app. 450 grams
Operating temperature	-20°C - +75°C
Overvoltage protection	integrated
Reverse polarity protection	integrated
RSSI-Output ⁽¹⁾	0 - 4,5 VDC
Conformity	CE

(1) Receive Signal Strength Indicator



The product is in compliance with the requirements of the following European directive:

199/5/EC	Radio and Telecommunications Terminal Equipment (R&TTE)
2011/65/EU	Restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

The compliance with the requirements of the European Directive was proved by the application of the following harmonized standards:

R&TTE:	EN 300 330-2 V1.5.1 EN 301 489-1 V1.9.2 EN 301 489-3 V1.6.1 EN 50364:2010 EN 55011:2009+A1:2010 EN 60950-1:2006 + A11:2009 + A12:2011 + A1:2010 + A2:2013
RoHS:	EN 50581:2012


The object of the declaration described above is in conformity with Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

Telemetry System AXON J2D

AXON „J“-series telemetry systems as an overview

- AXON J1

robust 1-channel telemetry system
for strain gauge measurements,
analogue transmission



- AXON J1DB

digital 1-channel telemetry system
for strain gauge measurements with
monitoring of the rotor power supply



- AXON J2D

digital 2-channel telemetry system for
the simultaneous transmission of two
strain gauge signals



- AXON J2DT

digital 2-channel telemetry system for
the simultaneous transmission of one
strain gauge and one thermocouple signal



- AXON J1T

digital 1-channel telemetry system for
the transmission of one thermocouple
signal



- AXON J2T

digital 2-channel telemetry system for
the simultaneous transmission of two
thermocouple signals



- AXON J4T

digital 4-channel telemetry system for
the simultaneous transmission of four
thermocouple signals



- AXON J8T

digital 8-channel telemetry system for
the simultaneous transmission of eight
thermocouple signals



Applications


Telemetry System AXON J2D

Shaft applications for torque- and temperature measurements
planned in detail - professionally built - delivered quickly

Another focus of AXON is the production of customized torque- and temperature measurement shafts. Careful planning includes the preparation of release drawings, which allow the user to check all dimensions and details for execution.

The flexibility of the AXON telemetry systems enables the construction of measuring shafts that work in the most difficult space conditions.

Sensors and electronics are sealed in multiple layers. A high-strength glass fiber composite protects the application from water, oil and mechanical damage. Thus, the maintenance-free applications are ideally suited for long-term driving tests.



State-of-the-art technology
in a robust package



The flexible design options
of the AXON telemetry
systems allow countless
application variants.

- Telemetry
- Application
- Calibration

from one source
fast and reliable

**From development to
customized solutions -
all from one hand**

- Development and production
- Application of measurement shafts
- Strain gauge application and calibration



Whether by phone, e-mail or in person-
our support is always available for
questions about our systems - fast and
easy!

Our experienced engineers and
technicians will be happy to assist you
in planning your measurement tasks-
contact us!

Contents and illustrations of this datasheet have been
elaborated to the best of our knowledge and with
utmost diligence we reserve the right of error and technical
modifications.